

30NOV23

O'HARE EIGHT DEPARTURE

CHICAGO, ILLINOIS
CHICAGO O'HARE INTL (ORD)

**TOP ALTITUDE:
5000**

RADAR required.

CHICAGO DEP CON
WEST
126.625 327.075

IOWA CITY
116.2 IOW
Chan 109

SPECIAL INSTRUCTIONS: For appropriate departure control frequency, see graphic. Use frequency depicted within the sector where first navaid/fix for your route is located (sectors indicated by dashed lines; frequencies in dashed box within).

DUPAGE
108.4 DPA
Chan 21

NOONY
SIMMN
OLINN

PEKUE

CHICAGO
Chan 19 (Y)
GCO (108.25)

BACEN

DENNT

ACITO

CMSKY

EARND

CHICAGO DEP CON
SOUTH
126.625 327.075

ROBERTS
116.8 RBS
Chan 115

PEOTONE
113.2 EON
Chan 79

BADGER
116.4 BAE
Chan 111

NOTE: All turbo-jet departures in all directions, maintain 250K until advised by ATC.

CHICAGO DEP CON
EAST/NORTH
125.0 337.4

KEELER
116.6 ELX
Chan 113

CLNC DEL
121.6
CPDLC

EBAKE
DUFEE
MOBLE

GIPPER
115.4 GU
Chan 101

MSA ORD 25 NM
3400



TAKEOFF MINIMUMS

- Rwy 22R: NA - ATC.
- Rwys 4L/R, 9L/C/R, 10L/C/R, 22L, 28C/R: Standard.
- Rwy 27L/C: Standard with minimum climb of 220' per NM to 1800.
- Rwy 27R: Standard with minimum climb of 220' per NM to 1700.
- Rwy 28L: Standard with minimum climb of 210' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1300' prior to DER.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

2A025

O'HARE EIGHT DEPARTURE

AL-166 (FAA)

CHICAGO O'HARE INTL (ORD)
CHICAGO, ILLINOIS

O'HARE EIGHT DEPARTURE



DEPARTURE ROUTE DESCRIPTION

ALL AIRCRAFT: Expect RADAR vectors to first enroute navaid/fix.
Expect clearance to requested altitude/flight level ten minutes after departure.

ALL AIRCRAFT: Cross 5.5 DME arc of GCO DME at or above 3000, cross
8.5 DME arc of GCO DME at or above 4000, maintain 5000 or assigned altitude.
If unable to comply advise ATC as soon as possible prior to departure.

EC-3, 22 FEB 2024 to 21 MAR 2024

EC-3, 22 FEB 2024 to 21 MAR 2024